



Размеры даны в миллиметрах

ART. B--M----		
Вес нетто, Kg.	Вес в упакованном виде, Kg.	Объем в упакованном виде, m ³
min. 58,7 - max. 90,6	min. 60,7 - max. 158,6	min. 1 - max. 3,5

		B		
		800	900	1000
A	1200	BC8M X= 1190 (+10/-5) Y= 790 (+10/-5)	BC9M X= 1190 (+10/-5) Y= 890 (+10/-5)	BCAM X= 1190 (+10/-5) Y= 990 (+10/-5)
	1300	BD8M X= 1290 (+10/-5) Y= 790 (+10/-5)	BD9M X= 1290 (+10/-5) Y= 890 (+10/-5)	BDAM X= 1290 (+10/-5) Y= 990 (+10/-5)
	1400	BE8M X= 1390 (+10/-5) Y=790 (+10/-5)	BE9M X= 1390 (+10/-5) Y=890 (+10/-5)	BEAM X= 1390 (+10/-5) Y=990 (+10/-5)
	1500	BF8M X= 1490 (+10/-5) Y=790 (+10/-5)	BF9M X= 1490 (+10/-5) Y=890 (+10/-5)	BFAM X= 1490 (+10/-5) Y=990 (+10/-5)
	1600	BG8M X= 1590 (+10/-5) Y=790 (+10/-5)	BG9M X= 1590 (+10/-5) Y=890 (+10/-5)	BGAM X= 1590 (+10/-5) Y=990 (+10/-5)
	1700	BH8M X= 1690 (+10/-5) Y=790 (+10/-5)	BH9M X= 1690 (+10/-5) Y=890 (+10/-5)	BHAM X= 1690 (+10/-5) Y=990 (+10/-5)
	1800	BI8M X= 1790 (+10/-5) Y=790 (+10/-5)	BI9M X= 1790 (+10/-5) Y=890 (+10/-5)	BIAM X= 1790 (+10/-5) Y=990 (+10/-5)
	1900	BL8M X= 1890 (+10/-5) Y=790 (+10/-5)	BL9M X= 1890 (+10/-5) Y=890 (+10/-5)	BLAM X= 1890 (+10/-5) Y=990 (+10/-5)
	2000	BM8M X= 1990 (+10/-5) Y=790 (+10/-5)	BM9M X= 1990 (+10/-5) Y=890 (+10/-5)	BMAM X= 1990 (+10/-5) Y=990 (+10/-5)